Search

Volumes

Key Engineering Materials Vol. 855

DOI:				https://doi.org/10.4028/www.scientific.net/KEM.855						
ToC:						<u>Ta</u>	able (of Co	<u>ntents</u>	
Sea	arch									
<	1	2	3	4	5	•••	>	>>		
Pape	r Title									Page
Syn Nar Auth Fitri Mas Abst (LCC mc	thesi opanors: ana, I atsur ract:) and ore	<u>s an</u> rticle Malil Darm ie Ka Non- La _{1.8}	d Ma s c Anjo ninto, to dope 35Sr ₀ .	agne elh B , Taka d and 15Cu(etic C aqiya ayuk d stro O ₄ (LS	<mark>2hara</mark> a, Put i Kaw pontiur SCO1	acter au Ek ama m-do 5)) in	r <mark>izat</mark> a Dha ta, Ta ped la nanc	<u>on of La_{2-x}Sr_xCuO</u> 4 arma Putra, Resky Irfanita, ikashi Noji, Hidetaka Sato, anthanum cuprates (La ₂ CuO ₄ o-sized particles were	58
<u>Ann</u> <u>Nar</u> Autł Purr	ealir opai ors: ,	<u>ng Te</u> rticle Ahm	<u>empe</u> es Us ad Th	<u>eratu</u> sing_ nabib	ure E Beng Mut	<u>Effect</u> g <u>awa</u> parok	<u>ts in</u> in Sc , Hei	<u>Co-F</u> olo R ndri V	<u>Precipitated CoFe₂O₄ iver Fine Sediment</u> Vidiyandari, Utari, Budi	64

Abstract: In this study, the synthesis of CoFe₂O₄ by using the fine sediment of the Bengawan Solo River, Trucuk District, Bodjonegoro <u>...more</u>

Effect of Lanthanum Substituted CoFe _{2-x} La _x O ₄ on Change of Structure Parameter and Phase Formation Authors: Akmal Johan, Ari Adi Wisnu, Fitri Suryani Arsyad, Dedi Setiabudidaya Abstract: In this research, CoFe _{2-x} La _x O ₄ -based smart magnetic material has been developed which will be applied as a microwave absorbing more	70
The Structural and Morphological Properties of Nanosized Nd _(1-x) Sr _(x) MnO ₃ (x = 0; 0.5; 1) Manganite Authors: Amilita Medisa Dharmayanti, Qoimatul Mustaghfiroh, Dicky Rezky Munazat, Dhawud Sabilur Razaq, Budhy Kurniawan, Dwi Nanto, Djati Handoko Abstract: A set of nanoparticles NdSrMnO ₃ has been prepared base on sol-gel method. On A site, the nanoparticles were modified by more	78
Effect of Sintering in Nanosized SrMnO ₃ Perovskite by Sol-Gel Method Authors: Djati Handoko, Qoimatul Mustaghfiroh, Dicky Rezky Munazat, Dhawud Sabilur Razaq, Budhy Kurniawan, Dwi Nanto Abstract: Nanosized particles SrMnO ₃ perovskite was prepared by using sol gel method. The sintering temperature was modified to 700, 1000 and more	84
Effect of Hard Magnetic CoFe ₂ O ₄ Nanoparticles Additives on Improving Rheological Properties and Dispersion Stability of <u>Magnetorheological Fluids</u> Authors: Kacuk Cikal Nugroho, Wahid Sidik Sarifuddin, Budi Purnama, Ubaidillah, Nur Azmah Nordin, Saiful Amri Mazlan Abstract: Increasing dispersion stability is the main issue in recent research at magnetorheological (MR) fluids. The presentation of more	89

<u>Synthesis and Characterization of Polycrystalline Fe_{1.025}Se</u> <u>Prepared Using Mechanical Alloying Followed by Powder in a</u> <u>Sealed Tube Method</u> 96

Authors: Sigit Dwi Yudanto, Ryan Fitriandhani, Andika Widya Pramono, Agung Imaduddin, Budhy Kurniawan Abstract: In this work, preparation of Fe _{1.025} Se samples was done using a solid-state reaction. Iron and selenium powder were used as raw <u>more</u>	
Early Characterization of NdFeB and NdFeB /Co-Al Composites of Sintering Using SPS Authors: Salim Mustofa, Setyo Purwanto, Sumaryo, Bambang Sugeng, Toto Sudiro, Bambang Hermanto, Nanang Sudrajat Abstract: The purpose of this study is to obtain a permanent magnet end- product from NdFeB and NdFeB / Co-Al composite material from SPS more	102
Structural Change and Magnetic Properties of Mechanically Alloyed Spinel Ferrite CoFe ₂ O ₄ Authors: Novrita Idayanti, Dedi, Azwar Manaf Abstract: Magnetic property studies and the crystallite structures evolution of spinel ferrite CoFe ₂ O ₄ particles are reported in this paper. more	108
<u>Morphological and Structural Analysis of Nd₁(Fe)_{0.2}Ba_{1.8}Cu₃O_{7-δ} Oxide Material Authors: Eko Hadi Sujiono, Nurul Fitriyah Mahendi, Abdul Haris, M. Yusriadi Dahlan, Bunga Dara Amin, Samnur, Dirfan Zabrian Abstract: Nd₁(Fe)_{0.2}Ba_{1.8}Cu₃O_{7-δ} oxide material have been successfully synthesized by solid-state reaction with modified heat treatment process</u>	117

<u>...more</u>

Showing 11 to 20 of 52 Paper Titles

< 1 **2** 3 4 5 ... > >>

DISTRIBUTION & ACCESS FOR PUBLICATION INSIGHTS DOWNLOADS AROUTINS POLICY & ETHICS CONTACT US IMPRINT PRIVACY POLICY SITEMAP ALL CONFERENCES ALL SPECIAL ISSUES ALL NEWS

Scientific.Net is a registered brand of Trans Tech Publications Ltd © 2022 by Trans Tech Publications Ltd. All Rights Reserved

Morphological and Structural Analysis of Nd₁(Fe)_{0.2}Ba_{1.8}Cu₃O₇₋₅ Oxide Material

Eko Hadi Sujiono^{1,a}, Nurul Fitriyah Mahendi¹, Abdul Haris¹, M. Yusriadi Dahlan¹, Bunga Dara Amin¹, Samnur¹ and Dirfan Zabrian¹

¹Laboratory of Materials Physics, Department of Physics, Universitas Negeri Makassar, Makassar 90224, Indonesia

^ae.h.sujiono@unm.ac.id

Keywords: Solid-state reaction, Rietveld refinement, heat treatment, $Nd_1(Fe)_{0.2}Ba_{1.8}Cu_3O_{7-\delta}$ system.

Abstract. Nd₁(Fe)_{0.2}Ba_{1.8}Cu₃O_{7- δ} oxide material have been successfully synthesized by solid-state reaction with modified heat treatment process to improve the heat time efficiency, calcination at 950°C for six hours, sintering at 975°C fo six hours, and annealing at 450°C for six hours, respectively. The X-ray diffraction pattern shows that a single-phase form of Nd₁(Fe)_{0.2}Ba_{1.8}Cu₃O_{7- δ} is an orthorhombic (Pmmm) structure. The Rietveld refinement analysis found, the lattice parameter are a = 3.8758Å, b = 3.9101Å, and c = 11.7190Å with χ^2 = 1.394%. The SEM-EDAX image shows that the samples are form clusters with size estimates of 10 - 40µm, and the elemental composition of the oxide materials is Ba rich.

Introduction

Oxide-alloy material is one of the interest research topics in material physics and engineering. This material can be applying in daily life since the properties such as the optic, catalytic, electric, and magnetic. Such as Fe_3O_4 and some other oxide, the frequency of dielectric constant is on range 10 Hz - 1 MHz, the other is Y_2BaCuO_5 has critical current density $Jc = 10^4 \text{ A/cm}^2$. The research of oxide-alloy material has conducted with various systems. One of them is the BaCuO system (Barium Copper Oxide), such as TIBaCuO (TBCO), YBaCuO (YBCO) [1,2], and NdBaCuO (NBCO).

The NdBaCuO system has some excellent properties if compared to the other BaCuO system. Base on DTA shows how easily Nd dissolves in the BaCuO system rather Y because Y requires a higher temperature. NdBaCuO also has a high critical temperature, Tc = 96 K [3].

NdBa₂Cu₃O_{7- δ} (δ = 0.09) that has an orthorhombic crystal structure with space group Pmmm. Lattice constants from Rietveld refinement method are a = 3.8622Å, b = 3.9180Å, and c = 11.7711Å with cell volume V = 178.12 Å³[4]. On the other hands [5] was found that Nd_{1+x}Ba_{2-y}Cu₃O₆ (x = 0.01 – 0.1 and y = 0.03 – 0.1) has tetragonal crystal structure (space group P4/mmm) with a = 3.9056Å, c = 11.823Å dan V = 180.39 Å³. YBa₂Cu₃O_{7-x} and NdBa₂Cu₃O_{7-x} have perovskite orthorhombic structure [6]. It is interesting to examine the NdBaCuO crystal structure because both orthorhombic and tetragonal structures have both CuO layers, which can affect high critical temperatures and superconducting properties [7,8].

The influence of dopant additions also contributes to BaCuO's crystal structure, with x additions on $Y(Ba_{1-x}Sr_x)_2Cu_3O_w$, O_4 's coordinate (one of oxygen in CuO layer) changed from $(0, \frac{1}{2}, 0)$ to $(x, \frac{1}{2}, 0)$, the distance between Ba/Sr – O_4 decreases as Sr content increases [9]. This dopant selection base on dopant's ionic radii smaller than the doped material and both are bivalent. Other than that, Fe₂O₃ choose as a dopant to increase magnetic properties for NdBaCuO. Besides the structure, particle size also one of the keys for oxide-alloy material [10]. The NBCO oxide material with the smaller grain size, higher critical current density is caused by improving surface contact area [11]. Grain size and shape also affect angle change between copper oxide bonds [7].

Several methods have been used to synthesized NdBaCuO, such as TSSG, Polymerized complex, sol-gel, and solid-state reaction method. All of this method took much time for the heat treatment process, such as calcination, sintering, and annealing, with various time and the different

molar ratio [3, 10, 12, 13]. In recent research, perovskite oxide only took 6 - 24 h for the heat treatment process [14,15].

Therefore, information on the morphological and structural of oxide material is crucial to know the particle size. This paper described the characterization results of $Nd_1(Fe)_{0.2}Ba_{1.8}Cu_3O_{7-\delta}$ oxide material using XRD, and SEM-EDAX. The effect of the heat treatment process related to the size and morphology information has discussed.

Experiment

Nd₁Fe_xBa_{2-x}Cu₃O_{7-δ} has prepared by a solid-state reaction method. High purity of Nd₂O₃ powder (99.99%), BaCO₃(99.98%), CuO (99.99%), and Fe₂O₃(99.98%) were mixing and grinding together with molar ratio x = 0.2 in mortar and pestle for 3 hours to reach homogenous powder. The precursor was calcined at 950°C for 6 hours and regrinding for 5 hours [16]. Then, the mixture was sintered at 975°C and annealed at 450°C, each for 6 hours with oxygen flow [16].

Analysis of the XRD pattern was carried out using Match!3 software to know the phase and crystallography data. Furthermore, the Rietica software used for Rietveld refinement analysis of the lattice constants and Full-Width at Half Maximum (FWHM). After refinement analysis, the data used Diamond software for visualized and described the distance between atoms also the angles.

Result and Discussion

X-Ray Diffraction Analysis

After the heat treatment for 18 h, Nd₁Fe_{0.2}Ba_{1.8}Cu₃O_{7- $\delta}$ characterized by XRD. Peak pattern, as shown in figure 1, there are 11 peaks identified by the software. The Match! 3 has used, firstly we search for a similar pattern and the same phase as we have. Since there is no one similar phase database on Match! So we decided to the most similar peak pattern in our sample. It was NdBa₂Cu₃-O_{6.92} [12]. The most dominant peak was at 20° 32.41° (110/013), with an intensity of 570 cps. Crystallography data shows that the structure is orthorhombic with space group Pmmm.}



Fig. 1 XRD pattern of Nd(Fe)BaCuO (\blacklozenge = Nd(Fe)BaCuO).

To describe the crystal structure, the refinement performed by the Rietveld method using Rietica software. Figure 2 shows the calculated pattern noted with a red curve, similar to the measured pattern illustrated with the black curve. Table 1 presented the value of χ^2 is 1.394, and the χ^2 value of less than 4 is an accepted constant factor of refinement [17]. The atom occupancy of Ba decrease

from 0.250 to 0.247. It caused the addition of Fe dopant as we know Fe ionic radii smaller than Ba, also confirmed that the volume cell smaller than has been reported [12]. The visualization of Nd₁(Fe)_{0.2}Ba_{1.8}Cu₃O_{7- δ} oxide structure shown in figure 3. The most exciting aspect of the configuration is the existence of angular change between the copper oxide bonds (Cu-O-Cu layer) becomes more pointed when viewed from the a-axis (151.932°) and b-axis (141.962°). This change will affect the superconducting properties [7].



Fig. 2 The plot of the Rietveld refinement results by using Rietica for Nd(Fe)BaCuO at 2θ of 10-80°.



Fig. 3 Visualization atomic structure of Nd(Fe)BaCuO phase with molar ratio x = 0.2 and the lattice parameter is a = 3.8758Å, b = 3.9101Å, c = 11.7190Å.

Rietveld refinement also has a general parameter (U, V, W) that we have refined. Using this parameter, the FWHM defined with the following equation (1):

$$H = \left(U\tan^2\theta + V\tan\theta - W\right)^{\frac{1}{2}}$$
(1)

Which is H indicate of FWHM (Full Width at Half Maximum) the crystalline quality of oxide materials, smaller FWHM means higher crystalline quality [14]. The FWHM of this sample is 0.266° , and the crystal size is D = 4.952 Å.

Table 1 Refinement parameters of Nd(Fe)BaCuO oxide material.

$Nd_1(Fe)_{0.2}Ba_{1.8}Cu_3O_{7-\delta}$				
Space group	Pmmm			
Lattice constants				
а				
b	3.8758 Å			
с	3.9101 Å			
	11.7190 Å			
Volume	177.5987 Å ³			
n _{Ba}	0.247			
R _{wp}	25.05			
R _p	18.74			
χ^2	1.394			



Fig. 4 SEM images of sample Nd(Fe)BaCuO phase with the molar ratio of x = 0.2, a) the magnification is 1,000X, b) the magnification is 5,000X, c) the analyzed area marking with red rectangular, and d) EDAX spectrum of Nd(Fe)BaCuO sample.

SEM-EDAX Analysis

The SEM-EDAX image, as shown in figure 4 Nd(Fe)BaCuO, allegedly formed clusters with estimated size ranging from $10 - 40 \mu m$. The inhomogeneous clusters size probably caused by the heat treatment process of the powder sample. The image in figure 4b presents Nd(Fe)BaCuO grain size with the surface area marked by the heavier atoms that have lighter imaging. It was also marked in figure 4c related to the diffraction pattern of EDAX, as shown in figure 4d. This result confirmed that the sample has Ba-rich.

Summary

The Nd₁(Fe)_{0.2}Ba_{1.8}Cu₃O_{7- δ} has an orthorhombic structure with space group Pmmm. FWHM counted is 0.266°, and the crystal size is 4.952 Å. The Rietveld refinement method found the lattice parameter a = 3.8758Å, b = 3.9101Å, and c = 11.7190Å with reliable factor χ^2 <4. Dopant addition Fe/Ba affected the distance of the atoms, the formation of Cu-O-Cu layer; this phenomenon can affect the superconducting properties. The surface morphology of the sample shows the size of the cluster ranging between 10 – 40 µm with elemental composition is Ba-rich confirmed by EDAX data. The morphological and structural analysis indicates the time efficiency for the heat treatment process has found.

Acknowledgments

This research conducted as part of the research scheme of fundamental research fiscal year of 2019 funded by Directorate research and Community Services, Directorate General of Research and Development, Ministry of Research, Technology, and Higher Education, Republic of Indonesia.

References

- E. H. Sujiono, P. Arifin, M. Barmawi, YBa₂Cu₃O_{7-δ} thin films deposited by a vertical MOCVD reactor. Mater. Chem. Phys. 73 (2002) 47-50.
- [2] E. H. Sujiono, R. A. Sani, T. Saragih, P. Arifin, M. Barmawi, YBa₂Cu₃O_{7-δ} Thin Films Deposited by MOCVD Vertical Reactor with a Flow Guide. Physica Status Solidi (A) Applied Research. 187 (2001) 471-479.
- [3] M. Nakamura, Fabrication of NdBa₂Cu₃O₇ single crystals by the top-seeded solution-growth method in 1%, 21%, and 100% oxygen partial pressure atmosphere. Phys. C: Superconductivity. 260 (1996) 297-304.
- [4] H. Shaked, Structural, and superconducting properties of oxygen-deficient NdBa₂Cu₃O_{7-δ}. Phys. Rev. B: Condens. Matter. 41 (1990) 4173-4180.
- [5] M. Nakamura, M. Kambara, T. Umeda, Y. Shiohara, Effect of oxygen partial pressure on the neodymium solubility in BaCuO solvent. Phys. C Supercond. 266 (1996) 178-182.
- [6] F. Parmigiani, G. Samoggia, C. Calandra, F. Manghi, Surface stoichiometry, and valence electronic structure of YBa₂Cu₃O_{7-x}. J. Appl. Phys. 66 (1989) 5958-5961.
- [7] S. Mollah, B. Biswas, S. Haldar, A.K. Ghosh, Carrier concentration induced transformations, and existence of pseudogap in NdBa₂Cu₃O_{7-δ}. Phys. C Supercond. It is Appl. 539 (2017) 40-43.
- [8] Y. Xin, Z.Z. Sheng, Study on Zn-, Cd-, or Hg-addition into TlBaCuO. J. Appl. Phys. 68 (1990) 5289-5292.
- [9] F. Licci, A. Gauzzi, M. Marezio, G.P. Radaelli, R. Masini, C. Chaillout-Bougerol, Structural, and electronic effects of Sr substitution for Ba in Y(Ba₁ – _xSr_x)₂Cu₃O_w at varying *w*. Phys. Rev. B 58 (1998) 15208-15217.
- [10] E.H. Sujiono, Muharram, 2017. Nd₁(Fe)_xBa_{2-x}Cu₃O_y Metal Oxide Compound and Its Fabrication Method, Patent No. P00200800471 (*in Indonesia*)
- [11] W. Bieger, U. Wiesner, G. Krabbes, P. Schatzle, A. Bauer, P. Verges, Zelenina, Melt Texturing, and Properties Control of Nd_{1+y}Ba_{2-y}Cu₃O_x Bulk Materials. J. Low Temp. Phys. 105 (1996) 1445-1450.

- [12] V.V. Petrykin, E.A. Goodilin, J. Hester, E.A. Trofimenko, M. Kakihana, N.N. Oleynikov, Y.D. Tretyakov, Structural disorder, and superconductivity suppression in NdBa₂Cu₃O_z (z~7). Phys. C Supercond. 340 (2000) 16-32.
- [13] N. A. Humairah, D. Sartika, Muris, E. H. Sujiono, Effect of Molar Ratio on Crystal Structure and Surface Morphology of Nd(Fe)_xBa_{2-x}Cu₃O₇ Oxide Alloy by Solid-State Reaction Method. IOP Conf. Ser.: Mater. Sci. Eng. 367 (2018) 012047
- [14] D.D. Athayde, D.F. Souza, A.M.A. Silva, D. Vasconcelos, E.H.M. Nunes, J.C. Diniz da Costa, W.L. Vasconcelos, Review of perovskite ceramic synthesis and membrane preparation methods. Ceram. Int. 42 (2016) 6555–6571.
- [15] E.H. Sujiono, A.C.M. Said, M.Y. Dahlan, R.A. Imran, S. Samnur, Refinement Analysis using the Rietveld Method of Nd_{1.2}Fe₁O₃ Oxide Material Synthesized by Solid-State Reaction. J. Nano- Electron. Phys. 10 (2018) 02034-1-02034–4.
- [16] E.H. Sujiono, A. K. Khatimah, A. N. Hasanah, N. F. Mahendi, M. Y. Dahlan, N. A. Humairah, A. Irhamsyah, Nd(Fe)_{0.3}Ba_{1.7}Cu₃O_{7-δ} Oxide Material Crystal Structure and Morphological Analysis. Materials Today: Proceedings 13 (2019) 264-269.
- [17] E.H. Kisi, Rietveld analysis of powder diffraction patterns. Mater. Forum 18 (1994) 135-155.
- [18] G. Will, Powder Diffraction: The Rietveld Method and the Two-Stage Method, Springer, 2006.